

S.N.: 09/471,857  
Art Unit: 2611

**AMENDMENTS TO THE CLAIMS:**

This listing of the claims will replace all prior versions, and listings, of the claims in this application.

Please cancel claim 5 without prejudice.

**Listing of Claims:**

1. (Currently Amended) A method for receiving a signal, said method comprising the steps of:

receiving an RF signal, said received RF signal comprising a plurality of information channel signals each comprising different code division multiple access data spread using a different spreading code, wherein each of said plurality of information channel signals are transmitted in one of a plurality of transmission bands, and each of said plurality of information channel signals is carried on one of a plurality of carrier frequencies;

down-converting said received RF signal by a single down-converter to form an intermediate signal, wherein said single down-converter is arranged to receive said received RF signal and multiply said RF signal by a plurality of oscillator signals when operating in a first mode and multiply said RF signal by a single oscillator signal when operating in a second mode, wherein said intermediate signal comprises down-converted versions formed by the single down-converter of each of said plurality of information channel signals, and said down-converted versions of each of said plurality of information channel signals are generated from a plurality of frequencies, said down-converted versions of each of said plurality of information channel signals are within a common frequency spectrum; and

decoding said intermediate signal to extract data from said down-converted versions of each of said plurality of information channel signals.

2. (Cancelled)
3. (Cancelled)
4. (Cancelled)
5. (Canceled).

6. (Currently Amended) The method of claim 1, wherein ~~a~~ the frequency spacing between each adjacent pair of said plurality of carrier frequencies and between each adjacent pair of said plurality of oscillator signals ~~frequencies~~ is substantially the same.
7. (Original) The method of claim 1, wherein said common frequency spectrum comprises a first common frequency spectrum, and the step of decoding said intermediate signal comprises the step of forming a baseband signal by down-converting said first common frequency spectrum to a second common frequency spectrum, said second common frequency spectrum lower in frequency than said first common frequency spectrum.
8. (Original) The method of claim 7, wherein the step of forming said baseband signal further comprises down-converting the intermediate signal using a first oscillator signal to form a first baseband component signal and a second oscillator signal to form a second baseband component signal, the first and second oscillator signals each at a same frequency and a different phase.
9. (Original) The method of claim 8, wherein said first baseband component comprises a first folded signal and said second baseband component comprises a second folded signal, each folded signal having a frequency spectrum narrower than said first common frequency spectrum.
10. (Original) The method of claim 9 further comprising the steps of:
  - sampling said first baseband component to form a first digital representation;
  - sampling said second baseband component to form a second digital representation; and
  - combining said first and said second digital representations to form an unfolded signal, said unfolded signal having a frequency spectrum greater than the spectrum of the first folded signal.
11. (Original) The method of claim 1, wherein the step of receiving an RF signal comprises receiving an RF signal from a cellular radio base station.
12. (Original) The method of claim 1, further comprising the step of filtering said intermediate signal to attenuate at least one signal outside the common frequency spectrum before performing said step of down-converting.
13. (Currently Amended) A mobile radio telephone unit comprising:
  - an antenna configured to receive an RF signal, said received RF signal comprising a plurality of information channel signals, each comprising different code division multiple access

S.N.: 09/471,857  
Art Unit: 2611

data spread using a different spreading code, wherein each of said plurality of information channel signals is transmitted in one of a plurality of transmission bands, and each of said plurality of information channel signals is carried on one of a plurality of carrier frequencies;

a single down-converter operatively coupled to the antenna and configured to down-convert said RF signal to form an intermediate signal, wherein said single down-converter is arranged to receive said received RF signal and multiply said RF signal by a plurality of oscillator signals when operating in a first mode and multiply said RF signal by a single oscillator signal when operating in a second mode, wherein said intermediate signal comprises down-converted versions of each of said plurality of information channel signals, and said down-converted versions of each of said plurality of information channel signals are generated from a plurality of frequencies, said down-converted versions of each of said plurality of information channel signals are within a common frequency spectrum;

a decoder operatively coupled to the single down-converter and configured to decode said intermediate signal to extract data from said down-converted versions of each of said plurality of information channel signals.

14. (Cancelled)

15. (Currently Amended) The mobile radio telephone unit of claim 13, wherein said single down-converter is configured to down-convert each of said plurality of carrier frequencies by a plurality of oscillator signals ~~frequencies~~ having a lower frequency.

16. (Currently Amended) The mobile radio telephone unit of claim 13, wherein said single down-converter comprises an oscillator for generating the plurality of oscillator signals and the single oscillator signal ~~an oscillator signal comprising a plurality of oscillator frequencies~~, a ~~the~~ frequency spacing between each adjacent pair of said plurality of carrier frequencies and between each adjacent pair of said plurality of oscillator signals ~~frequencies~~ being substantially the same.

17. (Cancelled)

18. (Cancelled)

19. (Cancelled)

20. (Currently Amended) A CDMA receiver for operating in at least a first mode and a second mode, said CDMA receiver comprising:

an initial RF stage, said initial RF stage for outputting a received RF signal, said received

S.N.: 09/471,857  
Art Unit: 2611

RF signal comprising a plurality of information channel signals each comprising different code division multiple access data spread using a different spreading code, wherein each of said plurality of information channel signals are transmitted in one of a plurality of transmission bands, and each of said plurality of information channel signals is carried on one of a plurality of carrier frequencies;

an oscillator, said oscillator for generating a plurality of oscillator signals, each at a different frequency, when the receiver operates in the first mode and generating a single oscillator signal when the receiver operates in the second mode;

a single down-converter coupled to said initial RF stage and said oscillator, said single down-converter for receiving said received RF signal and multiplying said received RF signal by said plurality of oscillator signals when the receiver operates in the first mode, and multiplying said received RF signal by said single oscillator signal when the receiver operates in the second mode, to generate an intermediate signal; and

a baseband stage, coupled to said single down-converter, said baseband stage for processing said intermediate signal.

21. (Currently Amended) A base station unit comprising:

a receiver to receive an RF signal, said RF signal comprising a plurality of information channel signals, each comprising different code division multiple access data spread using a different spreading code, wherein each of said plurality of information channel signals is transmitted in one of a plurality of transmission bands, and each of said plurality of information channel signals is carried on one of a plurality of carrier frequencies; and

a single down-converter operatively coupled to said receiver and configured to down-convert said RF signal to form an intermediate signal, wherein said single down-converter is arranged to receive said received RF signal and multiply said RF signal by a plurality of oscillator signals when operating in a first mode and multiply said RF signal by a single oscillator signal when operating in a second mode, wherein said intermediate signal comprises down-converted versions of each of said plurality of information channel signals, and said down-converted versions of each of said plurality of information channel signals are generated from a plurality of frequencies, said down-converted versions of each of said plurality of information channel signals are within a common frequency spectrum.

22. (Currently Amended) The base station unit of claim 21, wherein said single down-converter comprises an oscillator for generating an oscillator signal comprising a plurality of oscillator frequencies, ~~a the~~ frequency spacing between each adjacent pair of said plurality of carrier frequencies and between each adjacent pair of said plurality of oscillator signals ~~frequencies~~ being substantially the same.

23. (Currently Amended) A chip apparatus comprising:

a receiver to receive an RF signal, said RF signal comprising a plurality of information channel signals, each comprising different code division multiple access data spread using a different spreading code, wherein each of said plurality of information channel signals is transmitted in one of a plurality of transmission bands, and each of said plurality of information channel signals is carried on one of a plurality of carrier frequencies; and

a single down-converter operatively coupled to said receiver and configured to down-convert said RF signal to form an intermediate signal, wherein said single down-converter is arranged to receive said received RF signal and multiply said RF signal by a plurality of oscillator signals when operating in a first mode and multiply said RF signal by a single oscillator signal when operating in a second mode, wherein said intermediate signal comprises down-converted versions of each of said plurality of information channel signals, and said down-converted versions of each of said plurality of information channel signals are generated from a plurality of frequencies, said down-converted versions of each of said plurality of information channel signals are within a common frequency spectrum.

24. (Currently Amended) The chip apparatus of claim 23, wherein said single down-converter comprises an oscillator for generating an oscillator signal comprising a plurality of oscillator frequencies, ~~a the~~ frequency spacing between each adjacent pair of said plurality of carrier frequencies and between each adjacent pair of said plurality of oscillator signals ~~frequencies~~ being substantially the same.

25. (Currently Amended) An apparatus comprising:

a means for receiving an RF signal, said RF signal comprising a plurality of information channel signals each comprising different code division multiple access data spread using a different spreading code, wherein each of said plurality of information channel signals are transmitted in one of a plurality of transmission bands, and each of said plurality of information

channel signals is carried on one of a plurality of carrier frequencies; and

single means for down-converting said RF signal to form an intermediate signal, wherein said single means for down-converting is arranged to receive said received RF signal and multiply said RF signal by a plurality of oscillator signals when operating in a first mode and multiply said RF signal by a single oscillator signal when operating in a second mode, wherein said intermediate signal comprises down-converted versions of each of said plurality of information channel signals, and said down-converted versions of each of said plurality of information channel signals are generated from a plurality of frequencies, said down-converted versions of each of said plurality of information channel signals are within a common frequency spectrum.

26. (Currently Amended) The apparatus of claim 25, wherein said single means for down-converting ~~down-converter~~ comprises an oscillator for generating an oscillator signal comprising a plurality of oscillator frequencies, a the frequency spacing between each adjacent pair of said plurality of carrier frequencies and between each adjacent pair of said plurality of oscillator signals frequencies being substantially the same.

27. (Currently Amended) The mobile radio telephone unit of claim 13, wherein each down-converted version is processed by circuitry that processes all other down-converted versions from the down-converter to the decoder.

28. (New) The method of claim 1, further comprising amplifying, filtering, and amplifying the received RF signal before down converting it.

29. (New) The mobile radio telephone unit of claim 13, further comprising a first filter, a first amplifier, a second filter, and a second amplifier, wherein the received RF signal is successively filtered, amplified, filtered, and amplified before being down converted by the single down converter.

30. (New) The mobile radio telephone unit of claim 29, further comprising a down converter that converts the down-converted received RF signal to in phase (I) and quadrature (Q) component signals.

31. (New) The mobile radio telephone unit of claim 13, further comprising an amplifier amplifying the received RF signal before it is down converted by the single down converter.

32. (New) The mobile radio telephone unit of claim 13, further comprising the oscillator for

S.N.: 09/471,857  
Art Unit: 2611

generating the plurality of oscillator signals.

33. (New) The mobile radio telephone unit of claim 32, wherein the oscillator comprises a synthesizer.

34. (New) The mobile radio telephone unit of claim 13, wherein each one of the received RF signal follows a single path to the down-converter.

35. (New) The method of claim 1, wherein the intermediate frequency accommodates multiple intermediate frequency bands.

36. (New) The mobile radio telephone unit of claim 32, wherein the oscillator comprises a mixer.

37. (New) The chip apparatus of claim 23, wherein the chip apparatus is comprised of at least one integrated circuit.

38. (New) The chip apparatus of claim 23, wherein the chip apparatus is comprised of a single integrated circuit chip.

39. (New) The chip apparatus of claim 38, further comprising a down converter that converts the down-converted received RF signal to in phase (I) and quadrature (Q) component signals.

40. (New) The chip apparatus of claim 39, further comprising a first filter, a first amplifier, a second filter, and a second amplifier, wherein the received RF signal is successively filtered, amplified, filtered, and amplified in a single signal path before being down converted by the single down converter.